



# SPECIFICATIONS

Oil-Free Reciprocating Air Compressor	DATE	11-0421-
	CUSTOMER	
	MODEL No.	CFPS37-8.5
<b>1. BASIC COMP.</b>		
Model	F373CP-10-J	
Cylinder Bore × Stroke × Number	75×70×2	
Fly wheel dia.	370 mm	
Compressed fluid	Atmosphere (air)	
Compressed method	Oil free Reciprocating, One Stage	
Cooling method	Air cooled	
Operation control	Pressure Switch	
Control pressure	0.65~0.85 MPa	
Free air delivery ※1	360 L/min	
Air end rotation speed	1090 min <sup>-1</sup>	
Driving method	V-Belt Driven	
Discharge air outlet	Rc 3/8	
Air temperature set outlet	Atmosphere + 40°C less than	
Noise level (1.5m from the front) ※2	59 dB(A)	
<b>2. AIR TANK</b>		
Volume	62 L	
Max. Operating pressure	0.85 MPa	
<b>3. MOTOR</b>		
Type of motor	F Class insulation 4 pole	
Output power	3.7 kW	
Electric source	Three phase AC 220, 380, 440V / 60Hz	
Rated current (60Hz)	220V : 14.2A 380V : 8.2A 440V : 7.1A	
Starter method	Magnetic contactor direct start	
<b>4. PROTECTION</b>		
Over current stop	Thermal Relay (OCR)	
<b>5. OTHERS</b>		
Dimension (L x W x H) ※3	890 x 655 x 985 mm	
Approx. weight	159 kg	
Accessories	Instruction manual	
<b>REMARK</b>		
※1. Air delivery is discharged air volume at 0.85MPa converted into atmospheric pressure.		
※2. Noise level is measured at an anechoic room under loading operation.		
※3. The dimension is outer size excluding ball valve.		