

<b>Booster Compressor</b>	DATE	09-0115-09
	CUSTOMER	
	MODEL No.	CLBS75-30
<b>1. BASIC COMP.</b>		
Model	BRL75-30	
Cylinder Bore × Stroke × Number		
Compressed fluid	Atmosphere (air) or Nitrogen Gas	
Compressed method	Oil Type Reciprocating, One Stage	
Cooling method	Air cooled	
Operation control	Computer assisted dual control	
Pressure range intake air/gas	0.5 ~ 1.0 Mpa	
Control pressure	2.8 ~ 3.0 MPa	
Free air delivery ※1	2100 L/min	
Air end rotation speed	1040 min <sup>-1</sup>	
Driving method	V-Belt Driven	
Discharge air outlet	Rc 3/4	
Air temperature set outlet	Atmosphere + 30°C less than	
Noise level (1.5m from the front) ※2	56 dB(A)	
<b>2. AIR TANK</b>		
Volume	70L	
Max. Operating pressure		
<b>3. MOTOR</b>		
Type of motor	B Class insulation 4 pole (Mitsubishi 製)	
Output power	7.5 kW	
Electric source	Three phase AC 380V / 60Hz ( 220, 440V is Option)	
Rated current (60Hz)	380V : 16.3A	
Starter method	Magnetic contactor direct start	
<b>4. PROTECTION</b>		
Over current stop	Thermal Relay (OCR)	
<b>5. OTHERS</b>		
Dimension (L x W x H) ※3	1230 x 870 x 1115 mm	
Approx. weight	375 kg	
Accessories	Instruction manual	

## REMARK

※1. Air delivery is discharged air volume at 3.0MPa converted into atmospheric pressure.

※2. Noise level is measured at an anechoic room under loading operation.

※3. The dimension is outer size excluding ball valve.